



**Ultrafiltration membrane and method for producing the same, dope composition used for the same**

**Patent number:** EP1080777  
**Publication date:** 2001-03-07  
**Inventor:** MATSUMOTO KENJI (US); HAMADA TOSHIMITSU (US); IKEYAMA NORIO (US); OGURISU TATSUYA (US)  
**Applicant:** NITTO DENKO CORP (JP)  
**Classification:**  
- **international:** B01D67/00; B01D71/68; C08L81/06; B01D67/00; B01D71/00; C08L81/00; (IPC1-7): B01D71/68; B01D61/14; C08G75/23  
- **european:** B01D67/00F10; B01D71/68; C08L81/06  
**Application number:** EP20000118758 20000830  
**Priority number(s):** US19990387573 19990831

**Also published as:**

 JP2001070767 (/)

**Cited documents:**

 US5879554  
 US5919370  
 US5246582

**Report a data error he**

**Abstract of EP1080777**

An ultrafiltration membrane comprises a composition including 40-99.5 weight % of polyethersulfone, 0.1-50 weight % of polyvinylpyrrolidone and 0.1-40 weight % of sulfonated polyethersulfone. This composition can form an ultrafiltration membrane suitable for treatment of surface water. The ultrafiltration membrane is hydrophilic and resistant to contamination, so it can be used for various purposes such as purification of water from rivers, wells and seas, and it can also be used to provide general industrial water, and to treat waste water or the like. The present invention further provides a dope composition and a method for producing ultrafiltration membranes.

---

Data supplied from the **esp@cenet** database - Worldwide